

Varnish

PRODUCT DESCRIPTION

The Le Tonkinois varnish formula is based on a centuries-old tradition of protecting wood and metals. Le Tonkinois is a product of the highest purity and is produced exclusively from the finest linseed and tung oil. It is an oil that is unsurpassed by any chemical product.

SCOPE OF APPLICATION	When applied to wood and degreased metals, Le Tonkinois Vernis provides long-lasting protection and offers high UV resistance. Highly effective even over many years in extreme weather conditions. Le Tonkinois Vernis is the perfect protection for all types of wood, both indoors and outdoors, preserving the wood's natural, warm character even under extreme climatic conditions. Natural surfaces impress with their beautiful wood grain, which is further enhanced by Le Tonkinois.
PROCESSING	Ready to use. Stir well before use. Do not dilute. Apply with a brush or flat brush. For spray application, the varnish may be diluted with a maximum of 10% Le Tonkinois thinner. A grit size of 180–240 is recommended for sanding. Do not apply at temperatures below 12°C. Coats should always be applied thinly by roller or brush, and only one coat should be applied per day. Particularly well suited for use in the conservation of historic buildings.
USAGE	30–50 ml/m ² , 20 m ² /litre, per coat, depending on the surface condition and absorbency of the substrate, based on smooth, planed or sanded surfaces. Absorbent substrates may result in higher consumption rates for the first coat.
DRYING TIME	At 20°C and moderate humidity, the surface is dry after 6–8 hours; if possible, wait 24 hours before applying a further coat. Low temperatures, high humidity and poor ventilation delay drying and promote the build-up of odours. Ensure good ventilation during application. Initially, subject surfaces to load only with care. Surfaces can be walked on after 3 days with 2–3 coats.
SUBSURFACE	Untreated timber, wood-based materials; may also be used on cork under certain conditions. Carefully sand rough timber surfaces. The timber surface must be free from dust and grease, clean, dry and frost-free (max. 15% moisture content).

INHALTSSTOFFE	Linseed oil, tung oil, natural resins, isoaliphates
VOC SAFETY NOTICE	The VOC content of this product is a maximum of 400 g/l.
STORAGE	Store in a tightly sealed container in a dry, cool place, away from frost.
SHELF LIFE	Unopened, in its original packaging, it has a shelf life of at least 5 years.
ENTSORGUNG	Dispose of product residues and packaging in accordance with local regulatory requirements. Only send completely empty cans for recycling.
SAFETY INSTRUCTIONS	Please refer to the relevant safety data sheet for safety-related information.
DISCLAIMER	The information contained in this publication is based on our careful research and testing and is provided to the best of our knowledge. It is intended solely for the information of our customers; however, it does not exempt them from carrying out their own independent assessment of the products described to determine their suitability for the intended processes and purposes, nor does it exempt them from the risk of infringing any third-party intellectual property rights. This information is therefore non-binding and, in particular, does not constitute any warranty of quality within the meaning of the law. We accept no liability for the accuracy and completeness of the information contained in this publication, nor for any other technical advice we may provide. In addition, we refer you to our General Terms and Conditions, which are available on request.
KONTAKT	Hermann Sachse GmbH Unter den Linden 10 10117 Berlin Mobil: +49 (0) 30 / 346 558 515 E-Mail: hallo@le-tonkinois.de

To achieve the best possible results, please refer to the technical data sheets for all products used. The information provided is based on our current knowledge and experience. However, it does not constitute a guarantee of product properties and does not give rise to any contractual relationship. Upon publication of this technical data sheet, all previous information ceases to be valid.