



## Pflegeöl

Transparent, easy application. The open-pored, silk-matt, hard-wearing and water-repellent surface is low-yellowing.



## Product description

### Application area

For the treatment of all oiled and waxed surfaces such as wood, cork and linoleum indoors to prevent the formation of running roads.

## Processing

### Processing

Stir / shake container well before use. Care oil is applied evenly and thinly with a short-pile floor mop. After 15 - 20 minutes, remove excess oil and polish surface with white pad. Heavily worn and worn, lean surfaces must be treated a second time with care oil. treated with maintenance oil a second time. Ensure optimum fresh air circulation during application and drying of the product! Otherwise odor nuisance possible!

### Usage

Consumption and coverage depend on the absorbency of the substrate. Consumption approx. 30 - 40 ml/m<sup>2</sup>. Yield 25 - 35 m<sup>2</sup>/ltr. Determine exact consumption on the object.

### Drying time

After 6 - 12 hours (20°C, humidity 50 - 55%) dry, sandable and recoatable. Floors can be carefully loaded after 1 day. Full loading after 7 - 14 days.

### Cleaning the tools

Immediately after use with Le Tonkinois Verdünner.

# TECHNICAL DATA SHEET

Pflegeöl



## Substrates and their pretreatment

---

Underground	clean and dry
-------------	---------------

## Product information

---

Ingredients	Aromatics free hydrocarbons; cooking from derizole oil, tung oil and rosin; cooking from linseed oil stand oil, tung oil and rosin; talc; kaolin; zinc oxide; bentonite; amide wax; dryers without cobalt.
-------------	--

---

VOC Safety Notice	VOC content of this product is max. 550 g/l. The EU limit is max. 700 g/l. (Category "f" as of 2010.)
-------------------	--

---

Storage	Keep well closed and out of reach of children. Store in a cool and dry place, but frost-free.
---------	---

---

Shelf life	Shelf life unopened at least 5 years.
------------	---------------------------------------

---

Disposal	In accordance with local, official regulations. Dried up product residues can be disposed of with household waste.
----------	--

---

Safety instructions	For safety-relevant information, please refer to the corresponding safety data sheet.  Natural paints have a characteristic odor due to the vegetable oils used. Ensure good ventilation during processing. Drying oils can ignite spontaneously. Therefore, do not crumple up rags contaminated with this product, but let them dry spread out or soak them in water before disposing of them.
---------------------	---

To achieve optimum results, please observe the technical data sheets of all products used.  
The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.