Impression

PRODUCT DESCRIPTION

For pre-treatment/priming of absorbent surfaces or simply for treating and finishing timber indoors. Le Tonkinois Impression is a colourless, natural primer oil for impregnating timber. It penetrates deep into the timber and hardens it. Indoors, it provides ideal protection against liquids, dirt and wear and tear. Outdoors, it is the perfect primer for subsequent coating with Le Tonkinois varnishes. Thanks to its excellent penetrating power, the capillaries of the wood are sealed, which significantly reduces the wood's tendency to swell and minimises damage to the finish. Impression provides excellent adhesion for all wood protection paints and ensures that the pigments in subsequent coats remain where they belong – on the surface. This guarantees optimum protection against the damaging effects of UV light.

SCOPE OF APPLICATION	Vorstreichöl/Grundierung für alle saugenden und nicht saugenden, maßhaltigen und nichtmaßhaltigen Hölzern mit und ohne Erdkontakt wie: Fenster, Türen, Garagentore, Dachuntersichten, Holzverschalungen, Gartenzäune, Parkettböden und auf allen Hölzern im Innen- & Außenbereich.
PROCESSING	Ready to use; do not dilute. Apply with a brush or flat brush. Do not apply at temperatures below 12°C. Stir well before use. Apply the oil generously and evenly. After a short application time, spread any excess oil again with the brush, or dab it off with a lint-free cloth or rub it off gently. Particular care must be taken to ensure even application, especially on cork. One application is sufficient for pre-treatment; for final treatments indoors, two applications should be carried out, depending on the absorbency of the wood.
USAGE	30–50 ml/m^2 per coat, depending on the surface condition and absorbency of the substrate, based on smooth, planed or sanded surfaces. Absorbent substrates may require a higher amount of paint for the first coat. On average, 1 litre covers 20 m^2.
DRYING TIME	At 20°C and moderate humidity, the surface will be dry after 6–8 hours; however, wait 12 hours if possible before applying a further coat. Low temperatures, high humidity and poor ventilation will delay drying and may cause odours to develop. Ensure good ventilation during application. Avoid placing heavy loads on the surface initially.
SUBSURFACE	Untreated timber, wood-based materials, and, to a limited extent, cork. Carefully sand rough timber surfaces. The timber surface must be free from dust and grease, clean, dry and frost-free (max. 15% moisture cont-

INGREDIENTS	Linseed oil, tung oil, natural resins, isoaliphates
VOC SAFETY NOTICE	The VOC content of this product is a maximum of 400 g/l.
STORAGE	Store in a tightly sealed container in a dry, cool place, away from frost.
SAFETY INSTRUCTIONS	Please refer to the relevant safety data sheet for safety-related information.
DISCLAIMER	The information contained in this publication is based on our careful research and testing and is provided to the best of our knowledge. It is intended solely for the information of our customers; however, it does not exempt them from carrying out their own independent assessment of the products described to determine their suitability for the intended processes and purposes, nor does it exempt them from the risk of infringing any third-party intellectual property rights. This information is therefore non-binding and, in particular, does not constitute any warranty of quality within the meaning of the law. We accept no liability for the accuracy and completeness of the information contained in this publication, nor for any other technical advice we may provide. In addition, we refer you to our General Terms and Conditions, which are available on request.
CONTACT	Hermann Sachse GmbH Unter den Linden 10 10117 Berlin Mobil: +49 (0) 30 / 346 558 515 E-Mail: hallo@le-tonkinois.de

To achieve the best possible results, please refer to the technical data sheets for all products used. The information provided is based on our current knowledge and experience. However, it does not constitute a guarantee of product properties and does not give rise to any contractual relationship. Upon publication of this technical data sheet, all previous information ceases to be valid.