Parquets

PRODUCT DESCRIPTION

Le Tonkinois Parquets is an open-pored varnish with excellent penetration. As the oil penetrates the capillaries of the wood, swelling and shrinkage are significantly reduced, thereby providing long-lasting protection against abrasion and wear, as well as high UV resistance.

SCOPE OF APPLICATION	Le Tonkinois Parquets offers the perfect protection for any type of indoor wood, preserving the wood's natural, warm character for virtually an unlimited period of time. Natural finishes impress with their beautiful wood grain, which is further enhanced by Le Tonkinois.
PROCESSING	Ready to use. Stir well before use. Do not dilute. Apply with a brush, flat brush or spray. Depending on the type of wood, at least 2–3 coats are recommended. For sanding work, such as intermediate sanding, a grit of 180–240 is recommended. Do not apply at temperatures below 12°C. Coats should always be applied thinly by roller or brush, and only one coat should be applied per day. Thoroughly sand parquet or floorboards. Allow at least one day between coats, depending on drying times. For very soft woods, it is advisable to apply the primer coat using Le Tonkinois Impression, as this oil penetrates very deeply, seals the capillaries and hardens the wood. The oil should be applied in thin layers using a floor varnish roller.
CONSUMPTION	30–50 ml/m^2, 20 m^2/litre per coat, depending on the surface condition and absorbency of the substrate, based on smooth, planed or sanded surfaces. Absorbent substrates may require a higher amount of product for the first coat.
DRYING TIME	At 20°C and moderate humidity, the surface will be dry after 6–8 hours; if possible, wait 24 hours before applying a further coat. Low temperatures, high humidity and poor ventilation will delay drying and encourage the build-up of odours. Ensure good ventilation during application. Initially, subject the surface to loads only with care.
SUBSTRATE	Untreated timber, wood-based materials, and, to a limited extent, cork. Sand timber substrates thoroughly. The timber surface must be free from dust and grease, clean, dry and frost-free (max. 15% moisture content).

INGREDIENTS	Linseed oil, tung oil, natural resins, isoaliphates
VOC SAFETY NOTICE	The VOC content of this product is a maximum of 400 g/l. The EU limit is 500 g/l.
STORAGE	Store in a tightly sealed container in a dry, cool place, away from frost.
SHELF LIFE	Unopened, in its original packaging, it has a shelf life of at least 5 years.
DISPOSAL	Dispose of product residues and packaging in accordance with local regulatory requirements. Only send completely empty cans for recycling.
SAFETY INSTRUCTIONS	Please refer to the relevant safety data sheet for safety-related information.
DISCLAIMER	The information contained in this publication is based on our careful research and testing and is provided to the best of our knowledge. It is intended solely for the information of our customers; however, it does not exempt them from carrying out their own independent assessment of the products described to determine their suitability for the intended processes and purposes, nor does it exempt them from the risk of infringing any third-party intellectual property rights. This information is therefore non-binding and, in particular, does not constitute any warranty of quality within the meaning of the law. We accept no liability for the accuracy and completeness of the information contained in this publication, nor for any other technical advice we may provide. In addition, we refer you to our General Terms and Conditions, which are available on request.
CONTACT	Hermann Sachse GmbH Unter den Linden 10 10117 Berlin Mobil: +49 (0) 30 / 346 558 515 E-Mail: hallo@le-tonkinois.de

To achieve the best possible results, please refer to the technical data sheets for all products used. The information provided is based on our current knowledge and experience. However, it does not constitute a guarantee of product properties and does not give rise to any contractual relationship. Upon publication of this technical data sheet, all previous information ceases to be valid.